




Features

- The plastic package carries Underwriters Laboratory Flammability Classification 94V-0
- Construction utilizes void-free molded plastic technique
- Low reverse leakage current
- High forward surge current capability
- Lead free in comply with EU RoHS 2011/65/EU directives



Mechanical Data

- Case:SMAW
- Terminal:Leads solderable per MIL-STD-750 Method 2026
- Polarity:Color band denotes cathode end
- Mounting Position:Any

Ordering Information

Part Number	Marking	Shipping	Reel
RHM540HW	540H	8000PCS Tape&Reel	13 inches

Maximum Ratings and Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase half-wave 60Hz,resistive or inductive load,for capacitive load current derate by 20%.

Rating	Symbol	RHM540HW'	Unit
Maximum repetitive peak reverse voltage	V_{RRM}	4000	V
Maximum RMS voltage	V_{RMS}	2800	V
Maximum DC blocking voltage	V_{DC}	4000	V
Maximum average forward rectified current 0.2"(5mm) lead length at $T_A=50^{\circ}C$	$I_{(AV)}$	1.5	A
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}	45	A
Maximum instantaneous forward voltage at 1.5A	V_F	2.0	V
Maximum DC reverse current $T_A=25^{\circ}C$ at rated DC blocking voltage $T_A=100^{\circ}C$	I_R	5 150	μA
Typical junction capacitance (Note1)	C_J	9	pF
Typical thermal resistance (Note2)	$R_{\theta JA}$	93	$^{\circ}C/W$
Operating junction and storage temperature range	T_J, T_{STG}	-50 to +150	$^{\circ}C$

Note:(1) Measured at 1MHz and applied reverse voltage of 4.0V D.C.

(2) P.C.B. mounted with 0.2" × 0.2" (5 mm × 5 mm) copper pad areas.



Characteristics Curve

FIG.1 FORWARD CURRENT DERATING CURVE




FIG.2 MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3 TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS






FIG.4 TYPICAL REVERSE CHARACTERISTICS






Package Outline




Suggested Pad Layout





Carrier Tape Dimensions

Unit : mm





Symbol	Spec	Symbol	Spec
W	12.00±0.10	P1	4.00±0.10
E	1.75±0.10	P2	2.00±0.05
F	5.50±0.05	T	0.25±0.02
D0	1.55±0.05	A0	2.60±0.10
D1	1.50±0.10	B0	5.70±0.10
P0	4.00±0.10	K0	2.00±0.05

Reel Dimensions

Unit : mm


13" Reel



D5	Φ330.0±2.0
D6	Φ13.5±0.5
H	2.5±1.0
W2	12±2.0


Quantity: 8000PCS

Packaging




SMAW

8000PCS/Reel




5Reel/Inner Box
40KPCS/Inner Box



Dim(Unit:mm)
340mm*340mm*85mm

Dim(Unit:mm)
360mm*360mm*355mm




4 Boxes per carton
160KPCS per carton

13 inches Reel



Recommended Soldering Conditions



Recommended Conditions

Profile Feature	Pb-Free Assembly
Average ramp-up rate (T_L to T_P)	3°C/second max.
Preheat	
-Temperature Min ($T_{S\ min}$)	150°C
-Temperature Max ($T_{S\ max}$)	200°C
-Time (min to max) (t_s)	60-180 seconds
$T_{S\ max}$ to T_L	
-Ramp-up Rate	3°C/second max.
Time maintained above:	
-Temperature (T_L)	217°C
-Time (t_L)	60-150 seconds
Peak Temperature (T_P)	260°C
Time within 5°C of actual Peak Temperature (t_P)	20-40 seconds
Ramp-down Rate	6°C/second max.
Time 25°C to Peak Temperature	8 minutes max.