




### Features

- Top-side Cooling(TSC) Packaging technology
- Compact and Slim Packaging Solutions
- The plastic package carries Underwriters Laboratory Flammability Classification 94V-0
- For surface mounted applications
- Metal silicon junction,majority carrier conduction
- Low power loss,high efficiency
- High forward surge current capability
- Lead free in comply with EU RoHS 2011/65/EU directives



### Mechanical Data

- Case: SMHS
- Terminals: leads solderable per MIL-STD-750, Method 2026
- Polarity: Color band denotes cathode end
- Mounting Position: Any

### Ordering Information

| Part Number | Marking | Shipping           | Reel      |
|-------------|---------|--------------------|-----------|
| RH16HSL     | S16L    | 15000PCS Tape&Reel | 13 inches |

### Maximum Ratings and Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase half-wave 60Hz,resistive or inductive load,for capacitive load current derate by 20%.

| Parameter                                                                                             | Symbol                             | RH16HSL     | Unit          |
|-------------------------------------------------------------------------------------------------------|------------------------------------|-------------|---------------|
| Maximum repetitive peak reverse voltage                                                               | $V_{RRM}$                          | 60          | V             |
| Maximum RMS voltage                                                                                   | $V_{RMS}$                          | 42          | V             |
| Maximum DC blocking voltage                                                                           | $V_{DC}$                           | 60          | V             |
| Maximum average forward rectified current at $T_L$ (see fig.1)                                        | $I_{(AV)}$                         | 1           | A             |
| Peak forward surge current<br>8.3ms single half sine-wave superimposed on rated load (JEDEC Method)   | $I_{FSM}$                          | 50          | A             |
| Maximum instantaneous forward voltage at 1.0A                                                         | $V_F$                              | 0.50        | V             |
| Maximum DC reverse current<br>$T_A=25^{\circ}C$<br>at rated DC blocking voltage<br>$T_A=100^{\circ}C$ | $I_R$                              | 0.05<br>10  | mA            |
| Typical thermal resistance (Note1)                                                                    | $R_{\theta JA}$<br>$R_{\theta JC}$ | 62<br>7     | $^{\circ}C/W$ |
| Typical Junction Capacitance (Note2)                                                                  | $C_j$                              | 105         | pF            |
| Operating junction temperature range                                                                  | $T_J$                              | -55 to +125 | $^{\circ}C$   |
| Storage temperature range                                                                             | $T_{STG}$                          | -55 to +125 | $^{\circ}C$   |

Note: (1) P.C.B. mounted with 0.08" × 0.08"(2mmx2mm) copper pad areas.

(2) Measured at 1MHz and applied reverse voltage of 4V D.C



### Characteristics Curves

FIG. 1 FORWARD CURRENT DERATING CURVE




FIG. 2 MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG. 3 TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG. 4 TYPICAL REVERSE CHARACTERISTICS





FIG. 5 TYPICAL JUNCTION CAPACITANCE







Carrier Tape Dimensions

Unit : mm

| Symbol | Spec      | Symbol | Spec      |
|--------|-----------|--------|-----------|
| W      | 8.00±0.10 | P2     | 2.00±0.10 |
| E      | 1.75±0.10 | t      | 0.22±0.02 |
| F      | 3.50±0.10 | t1     | Min. 0.05 |
| D0     | 1.55±0.10 | A0     | 2.15±0.10 |
| D1     | 1.10±0.10 | B0     | 3.40±0.10 |
| P0     | 4.00±0.10 | K0     | 1.15±0.10 |
| P1     | 4.00±0.10 |        |           |

Reel Dimensions

Unit : mm

13" Reel

|                    |            |
|--------------------|------------|
| D5                 | Φ330.0±5.0 |
| D6                 | Φ13.5±0.5  |
| H                  | 2.5±1.0    |
| W2                 | 8.0±2.0    |
| Quantity: 15000PCS |            |

Packaging

SMHS

15000 PCS/Reel

5 Reel/Inner Box  
75K PCS/Inner Box

Dim(Unit:mm)  
340mm\*340mm\*85mm


Dim(Unit:mm)  
360mm\*360mm\*355mm

4 Boxes per carton  
300K PCS per carton

13 inches Reel



## Recommended Soldering Conditions



### Recommended Conditions

| Profile Feature                                      | Pb-Free Assembly |
|------------------------------------------------------|------------------|
| Average ramp-up rate ( $T_L$ to $T_P$ )              | 3°C/second max.  |
| Preheat                                              |                  |
| -Temperature Min ( $T_{S\ min}$ )                    | 150°C            |
| -Temperature Max ( $T_{S\ max}$ )                    | 200°C            |
| -Time (min to max) ( $t_s$ )                         | 60-180 seconds   |
| $T_{S\ max}$ to $T_L$                                |                  |
| -Ramp-up Rate                                        | 3°C/second max.  |
| Time maintained above:                               |                  |
| -Temperature ( $T_L$ )                               | 217°C            |
| -Time ( $t_L$ )                                      | 60-150 seconds   |
| Peak Temperature ( $T_P$ )                           | 260°C            |
| Time within 5°C of actual Peak Temperature ( $t_p$ ) | 20-40 seconds    |
| Ramp-down Rate                                       | 6°C/second max.  |
| Time 25°C to Peak Temperature                        | 8 minutes max.   |